

Twist-Lock® Devices

50 Ampere, 250 Volts DC and 600 Volts AC

3 Pole, 4 Wire Grounding

Plugs, Flanged Inlets, Connector Bodies and Receptacles**Important Note:** Catalog numbers HBL7379, HBL7764C, HBL7765C, HBL7958, HBL7968 are for replacement use only. See other singly rated 50A Twist-Lock®

devices in this section. HBL3700 series Twist-Lock devices do not interchange with any other devices in this section.

Plugs

Description	Cord Dia.	Catalog Numbers	
Nylon cover, thermoplastic polyester interior.	.920"-1.20" (23.68-30.48)	HBL3765C	HBL7765C

Accessories on page B-60.

Flanged Inlets

Description	Catalog Numbers
Zinc plated steel casing, with lift cover.	HBL3768 HBL7968
Zinc plated steel casing, without lift cover.	HBL3775 HBL7958

Connector Bodies




Description	Catalog Numbers
Nylon cover, thermoplastic polyester interior.	HBL3764C HBL7764C

Accessories on page B-60.

Receptacles

Description	Catalog Numbers
Black melamine.	HBL3769 HBL7379

Accessories on page B-60.

**HBL3765C****HBL3768****HBL3775****HBL3764C****HBL3769**